

LIFEGUARD 16

The LIFEGUARD 16 is the workhorse of the lifeguard family. At 32A three phase this can be fed from an LG83, 17 or as its own stand alone reticulation system.

The LIFEGUARD 16 comes with a great selection of high quality ABL socket outlets and with a weight of 15kg it is easy to see why it is the most popular choice on construction sites.

The LIFEGUARD 16 is manufactured from high impact polyethylene which is resistant to corrosion and especially suitable for use on rugged construction sites.

SPECIFICATIONS

SUPPLY INPUT POWER:	32A, 3 phase + N + E, 415VAC IEC
FREQUENCY:	50-60Hz
RCD:	4 pole, 30mA, 230 - 415VAC
SOCKET OUTLETS:	1 x 32A three phase 3P + N + E, 415VAC 1 x 16A single phase, 2P + E IEC 8 x 10/15A single phase 2P + E, 230VAC
INTERCONNECTION:	32A, 3 phase + N + E, 415VAC, CEE17, IEC309
MATERIALS:	Polyethylene enclosure
WEIGHT:	15kg

Expansion and Flexibility

The LIFEGUARD 16 system has the ability to interconnect in many ways to reticulate power throughout multi-storey and large single level construction areas.

Interconnection cables are rated at 32 amps and are of a waterproof design.

It is also available with supply input power ratings of up to 63 amps, and additional socket outlets to suit customer requirements.

LG16 systems used by the film industry can be fitted with specialist outlets and current monitoring facilities. Socket outlets may be varied in order to fit user specifications.

Can also be fitted with a hardwired chamber as per some site requirements.

LG16

