

PR4000

PR Power Mobile Lighting Tower



KEY FEATURES & BENEFITS

- ③ 4,200m² approx. illuminated area for maximum visibility
- ③ 360° mast rotation for maximum light coverage
- ③ Optional Auto Start/Stop System to automatically switch lights on and off according to light sensitivity. Optional warning beacon.
- ③ Multi-use tower fully equipped with a 9kW Generator
- ③ Manufactured to meet Australian Safety Standards
- ③ Weatherproof, soundproof and lockable enclosure for reduced noise and added security
- ③ Certified wind stability to 110km/h
- ③ Mast Safety - no crush points
- ③ Engine safety shutdown protection
- ③ Fully bunded to contain spills
- ③ 4x manual wind down stabiliser legs for added stability & safety
- ③ Long range 116 litre fuel tank
- ③ Forklift pockets and lifting points for easy manoeuvrability
- ③ Road ready trailer

TECHNICAL DATA

SPECIFICATIONS			
Light output	4 x 1000w		
Type of light	Metal Halide		
Maximum mast height	9m		
Mast lifting system	Hydraulic		
Mast rotation	360°		
Colour	White		
Auto Start/Stop Lighting System	LTR-01 Optional		
Warning Beacon	Optional		
ENGINE			
Engine	Kubota D1105-E		
Fuel tank	116 litres		
Fuel consumption	1.3 L/hr		
Operating hours	89hrs		
Noise rating	62dBA@7m		
TRAILER/CHASSIS			
Trailer	<ul style="list-style-type: none"> ③ Single axle, heavy duty ③ Adjustable towbar ③ Handbrake ③ Break away brake cable ③ Road ready 		
Certified wind stability	110km/h		
Stabilisers	4x Wind down stabiliser legs		
Dimensions (Mast fully retracted)	3400 x 1500 x 2330mm		
Dry weight	1115kg		
GENSET SPECIFICATIONS			
kW	Hz	V	rpm
9	50	240	1500